

EcoVerta Product Range Specifications

Specifications	<i>EcoVerta</i>	<i>EcoVerta Mixa</i>	<i>EcoVerta Protecta</i>
Depth mm	65	95	95
Length mm	145	195	250
Width mm	220	220	320
Weight Kg	3.7	7.2	13.1
Supply pressure static kPa	200-1200 max	200-1200 max	200-1200 max
Minimum supply flow rate litres/min	2	3	3
By-pass outlet pressure kPa max	1200 max	1200 max	1200 max
Water heater output water temperature °C	+40 to +80	+40 to +80	+40 to +80
By-pass switching temperature °C	Lower 30 (± 3°C)	Lower 30 (± 3°C)	Lower 30 (± 3°C)
	Upper 36 (± 3°C)	Upper 36 (± 3°C)	Upper 36 (± 3°C)
Maximum By-pass switching time	25 Seconds	25 Seconds	25 Seconds
Maximum leakage rate litres/min	0.05	0.05	0.05
Regulated outlet water temperature °C	N.A.	N.A.	44 (± 2°C)
Suitable for external mounting*	Yes	Yes	Yes
Fittings hoses & pipe sizes required ²	½" BSP	½" BSP	½" BSP
Rural tank water pre-filter required	Yes	Yes	Yes
Metropolitan water pre-filter required	Optional ¹	Optional ¹	Optional ¹

Specifications subject to change without notice

* Protection from freezing must be provided

¹ Subject to acceptable known mains water quality

² Different pipe sizes can be accommodated to special order

Flow Data Sheet

